

TITLE OF THE INVENTION

IMAGE DATA PROCESSING APPARATUS AND METHOD

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates generally to an image data processing apparatus and method for processing image data in a device having an image entry function, for example, a mobile telephone with
10 a camera, and more particularly to an image data processing unit and method for acquiring a stegano data embedded in an image, by use of image processing.

2. Description of the Related Arts

Recently, with the increasing use of the
15 Internet by mobile telephones, the development of mobile telephones mounting cameras, scanners or other image input devices has being made enthusiastically. By the use of such mobile telephones, image data acquired by image input
20 devices can be utilized, if the acquired image data is sent from the own mobile telephone to terminals, such as another mobile telephone or a personal computer, through the Internet or other communication networks. On the other hand, for
25 example, U.S. Patent No. 5,636,292 discloses a method

for utilizing image data in its Specification and Drawings, wherein an image input device such as a scanner or camera is connected to a personal computer. In this method for utilizing image data, images such as printed matters, in which steganographic encoded information (hereinafter referred to as "stegano data") is embedded, are read-out to a personal computer by an image input device, and the stegano data is detected and sent to a server. On the server side, a URL corresponding to the detected stegano data is searched, and the searched URL is sent back to the personal computer, and the personal computer makes access to a web site corresponding to the URL, for allowing information corresponding to the image to be displayed.

However, even if such a method for detecting stegano data and utilizing image data is to be carried out in the conventional mobile telephone with a camera, image processing for detecting stegano data that has been executed on a personal computer would not be able to be executed within a practical processing time due to the limitation of the processing performance by memory or a CPU that can be used for mobile telephones.

According to the present invention, there is provided an image data processing apparatus and method, that can execute complex image processing at a high speed, even if the processing performance on the image input side is low.

It is therefore the object to provide an image data processing apparatus comprising a first apparatus such as a mobile telephone which enters image data with embedded stegano data that cannot be recognized visually, the first apparatus sending the entered image data to the outside and receiving the result of processing from the outside for holding the same; and a second apparatus such as a server which effects data processing on the image data received from the first apparatus to acquire stegano data, the second apparatus sending the acquired stegano data as the result of processing to the first apparatus. Thus, the first apparatus can execute an analysis processing of image-embedded information at high speed, otherwise, such information would take a lot of processing time.

In this case, the first apparatus comprises an image data input unit which enters image data with stegano data embedded; a data sending unit which sends the entered image data to the outside; a result

data receiving unit which receives the processed
result data from the second apparatus; and a result
holding unit which holds the received result data,
whilst the second apparatus comprises an image data
5 receiving unit which receives image data from the
first apparatus; a data holding unit which holds the
received image data; an image data processing unit
which effects processing on image data to acquire
stegano data; and a result data sending unit which
10 sends the acquired stegano data as result data to the
first apparatus, and wherein a communication path
always or intermittently connects the first
apparatus and the second apparatus.

In the present invention, the second apparatus
15 converts the acquired stegano data into other
information, for sending as result data to the first
apparatus, whereas the first apparatus sends the
result data received from the second apparatus to an
external third apparatus, for receiving another
20 result of processing. Thus, stegano data acquired
by the second apparatus is converted to a URL, etc.,
such that a web site can be read through access to
the third apparatus, thereby eliminating the need of
embedding the vast amounts of information in the
25 image data. The first apparatus includes a

pre-processing unit which executes pre-processing of the entered image data, the pre-processing being part of image processing to be performed on the side of the second apparatus. Because of this provision, the load applied to the second apparatus can be reduced. The first apparatus splits the entered image data into a plurality of areas, to send some of the split image data to the second apparatus, whereas the second apparatus effects image processing on the some image data received from the first apparatus, the second apparatus, if stegano data cannot be acquired, sequentially requesting the first apparatus to make a re-transfer, for image processing, of image data of the remaining split areas until the second apparatus acquires stegano data. As the stegano data is usually embedded in a portion of the image, when a split portion is sequentially sent, instead of sending the image data as a whole, while the second apparatus is detecting the stegano data, load of image processing on the second apparatus side can be reduced, and communication speed can be increased. The first apparatus compresses image data entered and held, for sending to the second apparatus, and the second apparatus restores the compressed image data received from the first apparatus, for effecting.

image processing. Thus, by the compression of the data to be sent from the first apparatus to the second apparatus, the amount of data to be sent can be reduced, and the communication time can also be reduced.

5 The present invention provides an image data processing method comprising the steps of:

by a first apparatus, entering image data with embedded stegano data that cannot be recognized visually and sending the image data to a second
10 apparatus;

by a second apparatus, effecting data processing on the image data received from the first apparatus, to acquire stegano data; and

by the second apparatus, sending the acquired
15 stegano data as a result of processing to the first apparatus; and

by the first apparatus, receiving and holding the result data received from the second apparatus. The details of the image processing method will
20 become substantially the same as the case of the apparatus.

The present invention further provides an apparatus itself such as a mobile telephone having limited processing capabilities, the apparatus
25 comprising an image data input unit which enters

image data with stegano data embedded; a data sending unit which sends the entered image data to the outside; a result data receiving unit which receives stegano data as result data from the outside; and a
5 result holding unit which holds the received result data.

The above and other objects, aspects, features and advantages of the present invention will become more apparent from the following detailed
10 description when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram of a first embodiment
15 according to the present invention;

Fig. 2 is a diagram for describing image data processing operations according to Fig. 1;

Fig. 3 is a time chart of processing procedures of a first apparatus and a second apparatus shown in
20 Fig. 1;

Fig. 4 is a block diagram of a second embodiment according to the present invention;

Fig. 5 is a diagram for describing image data processing operations according to Fig. 4;

25 Fig. 6 is a time chart of processing procedures

of the first apparatus and the second apparatus shown in Fig. 4;

Fig. 7 is a block diagram of a third embodiment according to the present invention;

5 Fig. 8 is a time chart of processing procedures of a first apparatus and a second apparatus shown in Fig. 7;

Fig. 9 is a block diagram of a fourth embodiment according to the present invention;

10 Fig. 10 is a diagram for describing image data processing operations according to Fig. 9;

Figs. 11A and 11B are time charts of processing procedures of a first apparatus and a second apparatus shown in Fig. 9; and

15 Fig. 12 is a block diagram of a fifth embodiment according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is a block diagram of a first embodiment according to the present invention. An image data processing apparatus according to the present invention comprises a mobile telephone 10, which functions as a first apparatus, and a server 12, which functions as a second apparatus. On the mobile
20 telephone 10, an image data input unit 14, an image
25

data holding unit 16, an image data sending unit 18,
a result data receiving unit 20, a result data holding
unit 22, and a display unit 24 are provided. Also,
an image data receiving unit 26, an image data holding
5 unit 28, an image data processing unit 30, and a result
data sending unit 32 are provided on the server 12.
The image data input unit 14 of the mobile telephone
10 enters images using a CMOS sensor or CCD sensor.
The mobile telephone 10 comprises, for example, as
10 shown in Fig. 2, the display unit 24, a key operation
unit 38, and a camera 34. The image data processing
unit 30 provided on the server 12 performs image
processing for acquiring stegano data with respect
to the image data sent from the mobile telephone 10.
15 As the image data processing for acquiring the
stegano data, for example, the processing disclosed
in Specification and drawings of U.S. Patent No.
5,636,292 can be employed.

Fig. 2 shows brief image data processing
20 operations in a first embodiment according to Fig.
1. The camera 34 is provided as a single piece with
the mobile telephone 10, and images including
printing matters with stegano data embedded, which
is an object of the present invention, can be entered.
25 The image data entered through the camera 34 of the

mobile telephone 10 is sent to the server 12 through a communication line 42, and stegano data is acquired by the execution of a stegano data acquisition processing 40 in the server 12, so that the acquired
5 stegano data is sent back to the mobile telephone 10 through the communication line 42.

Fig. 3 is a time chart of processing procedure including communications exchanged between the mobile telephone 10 and server 12 in a first
10 embodiment shown in Fig. 1. Referring to Fig. 3, operations of a first embodiment shown in Fig. 1 is described as follows. When an image data input unit 14 takes a picture of image data, such as printed matters with stegano data embedded, and enters the
15 picture, the image data is held in an image data holding unit 16 at step S1, wherein the image data input unit 14 comprises a CMOS sensor and CCD sensor as the camera 34 provided on the mobile telephone. Then at step S2, an image data sending unit 18 sends
20 the data held in the image data holding unit 16 to the server 12 through a communication line 42-1. In sending, the destination information of the mobile telephone 10, which is to be the destination of the result of processing, is sent together with the image
25 data. In the server 12, after an image receiving unit

26 receives the image data and destination information sent from the mobile telephone 10 at step S101, the data is held in an image data holding unit 28. Next at step S102, the image data is called out of the image data holding unit 28, and, a stegano data acquisition processing is executed, for example, as disclosed in Specification and Drawings of U.S. Patent No. 5,636,292, for acquiring stegano data from the image data. The stegano data acquired by an image data processing unit 30 is sent to a result data sending unit 32, and at step S103, the stegano data is sent to the mobile telephone 10 as a result data, through a communication path 42-2, based on the destination information received together with the image data at step S103. The result data from the server 12 is received by a result data receiving unit 20 of the mobile telephone 10 at step S3, and held in a result data holding unit 22. The stegano data held in the result data holding unit 22 is given to a display unit 24, and at step S3, the stegano data received from the server 12 is displayed on the screen of the mobile telephone 10.

Fig. 4 is a block diagram of a second embodiment according to the present invention. This second embodiment is characterized in that the stegano data

acquired on the server side is further converted into the address of another apparatus, for example, URL, and returned to the mobile telephone. On the mobile telephone 10, an image data input unit 14, an image data holding unit 16, an image data sending unit 18, a result data receiving unit 20, and a result data holding unit 22 are provided, and the configuration for these units is the same as that in the first embodiment. In addition to these units, a WWW browser 48, and a HTTP transfer unit 50 are further provided on the mobile telephone 10. While on the server 12, in addition to an image data receiving unit 26, an image holding unit 28, an image data processing unit 30, and a result data sending unit 32, a data conversion unit 46 is further provided. The data conversion unit 46 has a function of converting the stegano data acquired by the image data processing unit 30 into a URL, that is the address of a WWW server 44 functioning as a third apparatus.

Fig. 5 is a diagram for briefly showing image data processing operations in the second embodiment shown in Fig. 4. In processing operations of this second embodiment, the image data including the stegano data entered through the camera 34 of the mobile telephone 10 is sent from the communication

line 42 to the server 12, and the stegano data is acquired by the execution of the stegano data acquisition processing 40, and the acquired data is further converted to the address, or URL of the WWW server, that is the third apparatus, through a URL conversion processing 52, and sent back to the mobile telephone 10 through the communication line 42.

Fig. 6 is a time chart of processing procedure including communications exchanged between the mobile telephone and server in the second embodiment shown in Fig. 4, and with reference to the figure, processing operations of the second embodiment are described as follows. The image data including the stegano data entered from the image data input unit 14 realized by the CMOS sensor or CCD sensor provided on the mobile telephone 10 as the camera 34 is sent to the server 12 from the image data sending unit 18 through the communication path 42-1 at step S2, after being entered and held in the image data holding unit 16 at step S1. At this time, together with the image data, the destination information is sent, indicating the destination, to which the result of processing is to be sent. At step S101, the server 12 allows the image data receiving unit 26 to receive the image data from the mobile telephone 10, and holds

the image data in the image data holding unit 28. Then at step S102, the server reads the image data out of the image data holding unit 28, and the image data processing unit 30 executes a stegano data acquisition processing. The stegano data acquired by the image data processing unit 30 is given to a data conversion unit 46 at step S103, for converting into a URL, the address of a WWW server 44, that is, to be a third apparatus, using of a conversion table, where the acquired stegano data is registered beforehand. The URL converted by the data conversion unit 46 is given to a result data sending unit 32 through the communication path 42-2 at step S104, and sent to the mobile telephone 10 through the communication path 42-1. At step S3, the mobile telephone 10 allows a result data receiving unit 20 to receive the URL converted from the stegano data as the result data from the server 12, and holds the URL in a result data holding unit 22. And at step S4, using the URL held in the result data holding unit 22, a WWW browser 48 gains access to a WWW server 44 through a HTTP transfer unit 50, and displays the home page specified by the URL of the WWW server 44 on the screen of the mobile telephone 10 such that the user can read it. In the second embodiment shown in Fig.

4, a data conversion unit 46 provided on the server 12 performs conversion from stegano data into a URL, or an address, however, another server may be provided as a fourth apparatus with the function of the data conversion unit 46, such that stegano data is sent to this server of the fourth apparatus from the mobile telephone 10 or server 12, for acquiring the address or URL of the WWW server 44 that is to be the third apparatus.

Fig. 7 is a block diagram of a third embodiment according to the present invention. This third embodiment is characterized in that part of image data processing is performed as pre-processing, since the side of the mobile telephone 10 acquires stegano data in the server 12. For the mobile telephone 10 as the first apparatus, an image input unit 14, an image data holding unit 16, an image data sending unit 18, a result data receiving unit 20, a result data holding unit 22, and a display unit 24 are provided, and the configuration for these units is the same as that in the first embodiment shown in Fig. 1. Furthermore, a pre-processing unit 54 is provided between the image data holding unit 16 and the image data sending unit 18. The pre-processing unit 54 performs pre-processing for converting the

color image data entered by the image data input unit 14 into, for example, binarized image data. In the embodiment shown in Fig. 1, the image data conversion unit 30 of the server 12 performs the conversion from color image data to binarized image data, however, in the third embodiment, this conversion is performed on the side of the mobile telephone 10. The server 12 as the second apparatus comprises an image data receiving unit 26, an image holding unit 28, an image data conversion unit 30, and a result data sending unit 32, and is basically the same as that in the first embodiment. However, since the image data conversion unit 30 includes the pre-processing unit 54 provided on the side of the mobile telephone 10, the data conversion unit 30 executes image data processing, except, for example, conversion processing from color image to binarized image, that is to be performed by the pre-processing unit 54, thus the processing load of the unit is reduced by the load assigned to the pre-processing unit.

Fig. 8 is a time chart of processing procedure including communications exchanged between the mobile telephone 10 and server 12 shown in Fig. 7, and referring to this time chart, operations of the third embodiment shown in Fig. 7 are described as

follows. At step S1, the mobile telephone 10 enters the image data on the image taken from printed matters including stegano data by an image input unit 14 comprising a CMOS sensor or CCD sensor, and holds the entered image data in an image data holding unit 16. Then at step S2, pre-processing is executed for converting the color image data entered by the pre-processing unit 54 as the image data into binarized image data. Next at step S3, the pre-processed binarized image data is sent from an image data sending unit 18 to the server 12 through a communication path 42-1. At this time, destination information is also sent at the same time, wherein the destination information indicates the destination to which the result data is to be sent. At step S101, the server 12 receives the binarized image data from the mobile telephone 10 with an image data receiving unit 26, and holds the received image data in an image data holding unit 28. Next at step S102, an image data conversion unit 30 reads out the binarized image data that is being held, and executes a stegano data acquisition processing as disclosed in Specification and Drawings of U.S. Patent No. 5,636,292. In this case, since the conversion from color image data to binarized image data has been

finished in pre-processing of the mobile telephone 10, processing following this conversion is executed. The stegano data acquired by the image data conversion unit 30 is sent from a result data sending unit 32 to the mobile telephone 10 through a communication path 42-2. At step S4, the mobile telephone 10 receives the stegano data from the server 12 with a result data receiving unit 20, as a result data, and holds the received result data in a result data holding unit 22. Eventually at step S5, the received stegano data is displayed on the screen of a display unit 24. If the number of servers 12 is not enough for accommodating the presence of a large number of mobile telephones, this pre-processing on the side of the mobile telephone 10 in the third embodiment shown in Fig. 7 can reduce the load of image data processing for acquiring stegano data on the side of the server 12, and enables quick image processing to be made so that the result of stegano data is returned in response to the processing demand from the mobile telephone 10.

Fig. 9 is a block diagram of a fourth embodiment according to the present invention. This fourth embodiment is characterized in that portion of image data including stegano data is sent from the mobile

telephone 10 for acquiring the result of processing. On the mobile telephone 10 as a first apparatus, an image data input unit 14, an image data holding unit 16, an image data sending unit 18, a result data receiving unit 20, a result data holding unit 22, and a display unit 24 are provided, and further an image data splitting unit 56 is additionally provided. The image data-splitting unit 56 splits the image data including the stegano data entered by the image data input unit 14 into a plurality of areas, and sends a portion of the split image data. If the stegano data cannot be acquired by sending of a portion of the image data, the image data-splitting unit repeatedly sends the remaining areas of the image data sequentially in response to a re-send request from the server 12, until stegano data is acquired. On the server 12 as a second apparatus, an image data receiving unit 26, an image data holding unit 28, an image data conversion unit 30, and a result data sending unit 32 are provided. Here, from the received image data, the image data conversion unit 30 executes a stegano data acquisition processing, for example, as disclosed in Specification and Drawings of U.S. Patent No. 5,636,292. At this time, if stegano data cannot be acquired, a re-send request

is made to the image data splitting unit 56 of the mobile telephone 10 through a communication path 42-3 for sending the remaining portions of the image data from the image data sending unit 18. This re-send request from the image data conversion unit 30 to the mobile telephone 10 is repeatedly made until stegano data is acquired on the side of the server 12.

Fig. 10 is a diagram for briefly describing image data processing operations in the fourth embodiment shown in Fig. 9. When printed matters or other images with stegano data embedded are entered by a camera 34 provided on the mobile telephone 10, after splitting the entered image data into a plurality of areas, the mobile telephone 10 sends the first split image data to the server 12 through a communication line 42, according to a specified sequence. If, for example, the image data is split into four areas, and a portion of the split image data is sent sequentially, the server 12 executes a stegano data acquisition processing 40 on the first received split data 58-1. If stegano data cannot be acquired by processing of this split image data 58-1, the server makes a re-send request to the mobile telephone 10, and receives the next split image data 58-2. When the split image data 58-2 is received in

response to the re-send request, the server executes the stegano data acquisition processing 40 on the image data including the split image data 58-1 which has been previously received and held. Even though
5 stegano data still cannot be acquired, the server has to make a re-send request to the mobile telephone 10 for acquiring a next split image data 58-3, and has to execute the stegano data acquisition processing 40. Usually, stegano data is embedded in printed
10 matters, such that the same embedded information is scattered over the entire image. Therefore, by sending of the image data split into a plurality of areas sequentially by the mobile telephone 10, not using of the total image, in a certain circumstances,
15 stegano data can be acquired only by sending of the first split image data 58-1. Even though stegano data cannot be acquired, stegano data will be acquired by sending of the remaining areas of the split image data following the first split area, thus
20 as a result, the server 12 can acquire stegano data, without the need of sending all image data.

Figs. 11A and 11B are time charts of processing procedure including communications exchanged between the mobile telephone 10 and server 12 in the
25 fourth embodiment shown in Fig. 9, and based on this

time chart, operations in the fourth embodiment shown in Fig. 9 are described as follows. Pictures of printed matters with stegano data embedded are taken by an image data input unit 14 realized by a CMOS sensor or CCD sensor provided on the mobile telephone 10 as a camera 34, and the image data is entered at step S1, and held in an image data holding unit 16. Then at step S2, the image data being held is split into a plurality of areas by an image data splitting unit 56, and part is taken out of the split image data, then at step S3, the split image data is sent to the server 12 through a communication path 42-1. At this time, destination information is simultaneously sent, wherein the destination information indicates the destination, to which the result of processing is to be sent. As to the split image data that should be sent first by the image splitting unit 56, for example, an area having a high possibility of stegano data being embedded may be preferentially selected from the total image data, and sent first. The server 12 allows an image data receiving unit 26 to receive part of the image data from the mobile telephone 10 at step S101, and holds the received image data in an image data holding unit 28, and at step S102, allows an image data conversion unit 30 to execute image

processing of part of the image data for acquiring stegano data. If stegano data cannot be acquired at step S103, by this image data processing, the server makes a re-transfer request to the mobile telephone 10 at step S104. Having received the re-transfer request from the server 12, the mobile telephone 10 takes part out of the remaining split image data at step S4, and allows an image data sending unit 18 to send the taken out image data to the server 12. After receiving and holding this second split image data at step S105, the server 12 executes image data processing for extracting stegano data at step S106. In this case, too, if stegano data cannot be acquired at step S107, the server makes a re-transfer request to the mobile telephone 10 at step S108, and repeatedly executes the same processing until stegano data is acquired. If stegano data is acquired at step S103 or S107, the server goes to step S109, and sends the acquired stegano data as a result data from a result data sending unit 32 to the mobile telephone 10 through a communication path 42-2. The mobile telephone 10 allows a result data receiving unit 20 to receive the stegano data as a result data at step S5, and holds the received data in a result data holding unit 22. Then at step S6, the received

stegano data is displayed on the screen of a display unit 24. Here, preferably the image data-splitting unit 56 splits image data into the size, which is less than or approximately equal to the accounting units of the mobile telephone 10. As described above, if the split size of image data is less than or approximately equal to the accounting units of the mobile telephone 10, in transferring the split image data from the mobile telephone 10 to the server 12, the communication route 42-1 is preferably intermittently connected only when the split image data is to be sent, but not normally connected. This method of intermittent connection can minimize cost required for the mobile telephone 10 transferring image data to the server for acquiring stegano data.

Fig. 12 is a block diagram of a fifth embodiment according to the present invention. This fifth embodiment is characterized in that the mobile telephone 10 compresses image data and sends to the server 12, and the server side restores the compressed image data and processes. To the mobile telephone 10, an image input unit 14, an image data holding unit 16, an image data sending unit 18, a result data receiving unit 20, a result data holding unit 22, and a display unit 24 are provided. In

addition, a data compression unit 60 is provided on the image data sending unit 18. As a data compression method by the data compression unit 60, such a compression method must be taken that there is no possibility of stegano data being broken by compression. For example, if the stegano data disclosed in Specification and Drawings of U.S. Patent No. 5,636,292 is used, a loss-less compression is employed. While on the side of the server 12, an image data receiving unit 26, an image data holding unit 28, an image data processing unit 30, and a result data sending unit 32 are provided. Furthermore, a data restoration unit 62 is provided on the image data receiving unit 26. The data restoration unit 62 implements a restoration method corresponding to the compression method of the data compression unit 60 on the mobile telephone side 10, and in this case, a restoration method is taken corresponding to the loss-less compression, a compression method that will not break stegano data. As described above, compressing and transferring image data in response to the request from the mobile telephone 10 to the server 12 for extracting stegano data can reduce the amount of image data to be sent, and furthermore, can reduce communication costs. Here, details of

processing operations of the fifth embodiment shown in Fig. 12 are the same as those of the first embodiment shown in Fig. 1, except that the data compression unit 60 compresses the data, and the data restoration unit 62 restores the compressed data.

As described above, according to the present invention, even if a first apparatus is a mobile telephone with a camera having a limited processing performance, the first apparatus can execute processing at high speed and acquire the result, even if the executing processing is an analysis processing of information embedded in image data, that takes a lot of processing time, if, in order to acquire the result of processing, the first apparatus sends image data including stegano data to a second apparatus, in other words, a server which has a high processing capability and is connected to the first apparatus through a communication path. Also, the conversion of the acquired stegano data that is sent by the server as the second apparatus to the address, or the URL of another third apparatus further enables abundant information on stegano data to be acquired through access to the third apparatus, thus the amount of information on stegano data to be embedded in image data can be reduced. Also, in sending image data from

the first apparatus to the second apparatus, part of image data is sent and a stegano data acquiring processing is performed. If stegano data cannot be acquired, a re-send request of the remaining image data is sequentially made and processed, such that the load of image processing on the second apparatus side can be reduced, and the speed of communication can be faster. Furthermore, when the first apparatus side performs part of image processing as pre-processing, wherein the image processing is required for stegano data acquiring processing in the second apparatus, the processing load of the second apparatus can be reduced. Furthermore, compressing and sending of image data from the first apparatus, and restoring of the compressed data on the side of the second apparatus can reduce the amount of data to be sent, and communication time, as well.

As to pre-processing on the side of the mobile telephone 10 in the third embodiment shown in Fig. 7, splitting and transfer of image data in the fourth embodiment shown in Fig. 9, and furthermore, compression and restoration of data in the fifth embodiment shown in Fig. 12, the first embodiment shown in Fig. 1 is cited as the object, however, in an embodiment where stegano data is converted to the

address or URL of a third apparatus as shown in Fig. 4, the above-described embodiments can be similarly combined.

The above-described embodiments cite the case
5 where a camera is employed for entering image, however, other than this, any appropriate image input processing including a scanner may be employed.

The above-described embodiments cite an example of a mobile telephone as a first apparatus,
10 however, the present invention is not limited to mobile telephones, but covers any appropriate apparatus, if the apparatus has a relatively low image processing performance.

Although as stegano data, the above-described
15 embodiments use by way of example the data as disclosed in Specification and Drawings of U.S. Patent No. 5,636,292, the present invention is not limited thereto, but is applicable intactly to any stegano data based on other embedding methods.

20 In addition, the above-described embodiments use by way of example the data conversion from stegano data acquired by the server to the address or URL of the third apparatus; however, the data conversion of present invention includes not only the address, but
25 also any other appropriate conversion objects.

The present invention covers any appropriate modifications without impairing the object and advantages thereof, and is not subject to any restriction by numerical values given in the above
5 embodiments.